


P-TYPE® Enhanced Service Advantage Cartridge HD Secondary Belt Cleaner

Reliable Cleaner with Improved Serviceability

The P-Type® ESAC combines the compact and highly efficient P-Type Secondary Cleaner with the Enhanced Service Advantage Cartridge. Not only simple to install using the versatile tensioner kit, the P-Type ESAC is also trouble-free to service, with the easy-to-use cartridge kit. The new cartridge now gives you control over maintenance with three easy-to-use removal options. The P-Type ESAC is the reliable choice for a great cleaner at the right price.



P-TYPE® with Enhanced Service Advantage Cartridge Heavy-Duty Secondary Belt Cleaner

Maximum Belt Speed

1000 FPM (5 M/sec)

Temperature Rating

-30° F to 180° F (-35° C to 82° C)

Usable Blade Wear Length


3/8" (9 mm)

Blade Material

Impact resistant, long-lasting tungsten carbide (C-Tip for mechanical fasteners, V-Tip for vulcanized belts)

Available for Belt Widths

24" to 120" (600 to 3000 mm)



SINGLE CARTRIDGE

Overall Pole Length

Cleaner size + 54" (1350 mm)

Maximum Conveyor Span

Cleaner size + 42" (1050 mm)

Ordering Information

PC SAC HD Secondary Cleaner C-Tips and Bolt Tensioner

Belt Width		Ordering Number	Item Code
in.	mm		
24	600	PC24-ESAC	77955
30	750	PC30-ESAC	77956
36	900	PC36-ESAC	77957
42	1050	PC42-ESAC	77958
48	1200	PC48-ESAC	77959
54	1350	PC54-ESAC	77960
60	1500	PC60-ESAC	77961
72	1800	PC72-ESAC	77962
60	1500	PC60-2ESAC	77963
72	1800	PC72-2ESAC	77964
84	2100	PC84-2ESAC	77965
96	2400	PC96-2ESAC	77966
120	3000	PC120-2ESAC	77967

Lead time: 1 working day

PV SAC HD Secondary Cleaner V-Tips and Bolt Tensioner

Belt Width		Ordering Number	Item Code
in.	mm		
24	600	PV24-ESAC	77981
30	750	PV30-ESAC	77982
36	900	PV36-ESAC	77983
42	1050	PV42-ESAC	77984
48	1200	PV48-ESAC	77985
54	1350	PV54-ESAC	77986
60	1500	PV60-ESAC	77987
72	1800	PV72-ESAC	77988
60	1500	PV60-2ESAC	77989
72	1800	PV72-2ESAC	77990
84	2100	PV84-2ESAC	77991
96	2400	PV96-2ESAC	77992
120	3000	PV120-2ESAC	77993

Lead time: 1 working day

Lead time: 15 working days

NOTE: For easy blade changeout, remove cartridge with worn blades and replace with new blade cartridge kit. New blades can then be installed in the old cartridge for the next changeout.

Blade Cartridge Kits with C-Tips (Incl. blades, cartridge, and bolts)


Belt Width		Ordering Number	Item Code
in.	mm		
24	600	P-CARK-C24/600	78072
30	750	P-CARK-C30/750	78073
36	900	P-CARK-C36/900	78074
42	1050	P-CARK-C42/1050	78075
48	1200	P-CARK-C48/1200	78076
54	1350	P-CARK-C54/1350	78077
60	1500	P-CARK-C60/1500	78078
72	1800	P-CARK-C72/1800	78079
60	1500	P-CARK2-C60/1500	78088
72	1800	P-CARK2-C72/1800	78089
84	2100	P-CARK2-C84/2100	78090
96	2400	P-CARK2-C96/2400	78091
120	3000	P-CARK2-C120/3000	78092

Lead time: 1 working day

Blade Cartridge Kits with V-Tips (Incl. blades, cartridge, and bolts)

Belt Width		Ordering Number	Item Code
in.	mm		
24	600	P-CARK-V24/600	78080
30	770	P-CARK-V30/770	78081
36	900	P-CARK-V36/900	78082
42	1050	P-CARK-V42/1050	78083
48	1200	P-CARK-V48/1200	78084
54	1350	P-CARK-V54/1350	78085
60	1500	P-CARK-V60/1500	78086
72	1800	P-CARK-V72/1800	78087
60	1500	P-CARK2-V60/1500	78093
72	1800	P-CARK2-V72/1800	78094
84	2100	P-CARK2-V84/2100	78095
96	2400	P-CARK2-V96/2400	78096
120	3000	P-CARK2-V120/3000	78097

Lead time: 1 working day



Horizontal Clearance Required

4-1/2" (114 mm)

Vertical Clearance Required

10-1/2" (267 mm) (Single Cartridge)

12-1/4" (311 mm) (Dual Cartridge)

Replacement Tips

Ordering Number	Item Code
ICT6	74535
PSA150	73156

Lead time: 1 working day

Tips Required per Cleaner Size

in.	mm	Tips Required
24	600	4
30	750	5
36	900	6
42	1050	7
48	1200	8
54	1350	9
60	1500	10
72	1800	12
84	2100	14
96	2400	16
120	3000	18



2525 Wisconsin Avenue • Downers Grove, IL 60515-4200 U.S.A.

Tel: (630) 971-0150 • Fax: (630) 971-1180 • E-mail: info@flexco.com • Web: www.flexco.com

Australia: 61-2-9680-3322 • China: 86-21-33528388 • England: 44-1274-600-942 • Germany: 49-7428-9406-0
India: 91-44-4354-2091 • Mexico: 52-55-5674-5326 • Singapore: 65-6281-7278 • South Africa: 27-11-608-4180

©2011 Flexible Steel Lacing Company. 06/11. For Reorder: X2421

Authorized Distributor:

